

- <u>Home</u>
- <u>Blog</u>
- <u>Study</u>
- Writing
- Projects
- <u>Connect</u>
- <u>About</u>

A tmux Primer

Home » Study » A tmux Primer

800	5. root :: seneca :: 192.73.232.138	8 (ssb)		
<pre>14 var express = require('express'); 13 var app = express(); 14 11 var quotes = [16 (author : 'Audrey Hepburn', text : 'Noth 16</pre>	1102920 Fir 174.125.176 174.125.176 1812220 Fir 1812220 Fir 181220 Fir 181200 Fir 181220 Fir 181200 Fir	<pre></pre>		
<pre>2 app.pt('/quote/random', function(req, re) 3 var id = Math.floor(Math.random() * quotes 4 var q = quotes(id); 5 res.json(q); 6)); 7)); 8 app.pet('/quote/:id', function(req, res) / 9 if(quotes.length <= req.params.id rec.; 10 res.statusCode = 404; 11 return res.send("Error 404: No quote found 12) 13 14 var q = quotes(req.params.id);</pre>	<pre>() (</pre>	0.7%] Tasks: 37. 29 thr: 1 running 0.7%] Load average: 0.60 0.01 0.00 0.0%] Uptime: 35 days, 86:43:50 0.6%] 1111/244803 124/284893 1		
15 res.json(q); NORMAL quote.js + unix utf-1	8 javascript 36% LN 15:3 14 SIGALRM Enterteend	M 30864 www-data 20 0 20844 2876 1372 S 0.0 0.1 1:54.0 30863 www-data 20 0 20856 2732 1380 S 0.0 0.1 1:53.4 Esclancel		
root;;seneca;;192.73.232.138 0:vi+		monitoring Sat 30 Nov 11:1		

- Intro
- Why Tmux?
 - What About Screen?
- Basics
 - <u>The tmux Shortcut</u>
 - Invocation
 - Show Sessions
 - Create a New Session
 - Attach to an Existing Session
 - Detaching from an Existing Session
- Configuration
- <u>Advanced</u>
 - Windows and Panes
- <u>Recommendations</u>
- <u>Shortcut Reference</u>

A tmux Primer

There are 4,257 tutorials on tmux. That's a rough number that I just made up. This one is designed to take you from "wtf tmux" to "omg tmux" with extreme haste.

Let's get started.

Why Tmux

tmux is useful to people in different ways. To me, it's most useful as a way to maintain persistent working states on remote servers—allowing you to detach and re-attach at will.

You could, for example, have a session on your server for hacking on a node REST API (my current project), and call it "nodeapi". And let us say that you are compiling something for it that will take two hours (work with me), but you're currently working at a coffee shop and you have to leave. tmux lets you simply detach from that session and come back to it later.

That's handy.

Others like to focus on how you can use tmux to have multiple panes within multiple windows within multiple tabs within multiple sessions. I don't do that. I like fewer of those—as few as possible, actually—and this guide will be focused on a simple *persistent-remote-sessions* model.

A remote computing lifestyle

Mobility is a central theme for tmux users. Many developers do all of their work from the server, and simply connect in from \$wherever to do it. tmux (and similar tools) allow you to work from a coffee shop in SF, start something building on the server, disconnect to take a flight, and then pick up that same task on the ground in NYC when you land.

A related advantage to this mobile approach is the fact that your client machine is not too terribly important. You can upgrade your laptop, clone a repo with your vim/tmux dotfiles in it, and you're back to your optimum computing environment in minutes rather than days.

Anyway, those are some reasons that people love tmux, but you don't have to make this lifestyle change in order to see its benefits.

What about screen?

Good question. tmux is a lot like screen, only better. The short answer for *how* it's better is that tmux is better designed to perform the same functions. Screen gets you there (kind of) but does so precariously.

Here are a few of the key advantages of tmux over screen:

- Screen is a largely dead project, and its code has significant issues
- Tmux is an active project with an active codebase
- Tmux is built to be truly client/server; screen emulates this behavior
- Tmux supports both emacs and vim shortcuts
- · Tmux supports auto-renaming windows
- Tmux is highly scriptable
- Window splitting is more advanced in tmux

Enough about that. Use tmux.

Basics

Now is a good time to mention that there is a universal tmux shortcut that lets you quickly perform many tasks.

The tmux shortcut

By default, tmux uses Ctrl-b as its shortcut activation chord, which enables you perform a number of functions quickly. Here are a few of the basics:

First you hit:

\$ Ctrl-b

...followed by a number of options that we'll talk about below. But get ready to use that Ctrl-b combo. Also consider remapping CAPSLOCK to CONTROL within your operating system; it makes the pinky walk for Ctrl-b quite nice.

Invocation

Right then. Let's start by running tmux. You want to do this from the system that you want to detach and re-attach to—which for me is usually a remote server.

\$ tmux

Simple enough. You now have a tmux session open that you can disconnect from and come back to later.

Show Sessions

Since the idea of tmux is having multiple sessions open, and being able to disconnect and reconnect to them as desired, we need to be able to see them quickly.

Via shortcut (by default Ctrl-b)

\$ Ctrl-b s

Via tmux command

\$ tmux ls

Either way you get the same thing:

0: 1 windows (created Thu Nov 28 06:12:52 2013) [80x24] (attached)

Create a new session

Now we're going to create a new session. You can do this with just the *new* command, or by providing an argument to it that serves as the session name. I recommend providing a session name, since organization is rather the point of tmux.

\$ tmux new -s session-name

Without naming the new session (not recommended)

\$ tmux new

Attaching to an existing session

Since we're going to be creating sessions with names, and we may have more than one, we want to be able to attach to them properly. There are a couple ways of doing this.

You can simply type tmux a and it'll connect you to the first available session.

\$ tmux a

Or you can attach to a specific session by providing an argument.

\$ tmux a -t session-name

Detaching from a session

You can detach from an existing session (so you can come back to it later) by sending the detach command.

\$ tmux detach

Or you can use the shortcut.

\$ Ctrl-b d

Killing a session

There are times when you'll want to destroy a session. This can be done using the following syntax, which is much the same as attachment:

\$ tmux kill-session -t session-name

[NOTE: You can kill windows the same way, but using kill-window instead. You can also kill tmux altogether with killall tmux.]

Configuration

As with most things in tech, you can get pretty silly with your tmux config. The common things to tinker with are:

- The primary tmux shortcut
- Your status bar
- Your various keyboard shortcuts

I went pretty Spartan with mine.

```
# Set a Ctrl-b shortcut for reloading your tmux config
bind r source-file ~/.tmux.conf
```

```
# Rename your terminals
set -g set-titles on
set -g set-titles-string '#(whoami)::#h::#(curl ipecho.net/plain;echo)'
```

```
# Status bar customization
set -g status-utf8 on
set -g status-bg black
set -g status-fg white
set -g status-interval 5
set -g status-left-length 90
set -g status-right-length 60
set -g status-left "#[fg=Green]#(whoami)#[fg=white]::#[fg=blue] \
```

(hostname - s)#[fg=white]::##[fg=yellow]#(curl ipecho.net/plain;echo)"

```
set -g status-justify left
set -g status-right '#[fg=Cyan]#S #[fg=white]%a %d %b %R'
```

One thing worth noting here is that I use ipecho.net to get my current WAN IP4 WAN address instead of icanhazip as most other tutorials have. It's just faster and less prone to error, from my experience.

[My current, updated configuration can be found here if you're interested.]

Advanced

1/9/2015

A tmux Primer

That covers how I usually use tmux, but I do often make use of some of the more powerful features.

Windows and Panes

9 O O 5. root	:: seneca :: 192.73.232.138 (ssh)						
14 var express = require('express');	102920 Firefox/3.0.4 chartbeat/uptimeping"						
13 var app = express();	74.125.176.54 [30/Nov/2013:11:13:12 -0800] "GET / HTTP/1.1" 200	74.125.176.54 [30/Nov/2013:11:13:12 -0800] "GET / HTTP/1.1" 200 1992 "-"					
12	"Mozilla/5.0 (Macintosh; U; Intel Mac OS X 10.5; en-US; rv:1.9.0.4)	"Mozilla/5.0 (Macintosh; U; Intel Mac OS X 10.5; en-US; rv:1.9.0.4) Gecko/200					
11 var quotes = [8102920 Firefox/3.0.4 chartbeat/uptimeping"						
10 { author : 'Audrey Hepburn', text : "Nothing is impossible, the	ord itse[107.21.81.38 [30/Nov/2013:11:13:14 -0800] "GET / HTTP/1.1" 301 1	78 "-"					
<pre>lf says 'I'm possible'!"},</pre>	ozilla/5.0 (Macintosh; U; Intel Mac OS X 10.5; en-US; rv:1.9.0.4) Get	cko/20					
9 { author : 'Walt Disney', text : "You may not realize it when it	happens, 02920 Firefox/3.0.4 chartbeat/uptimeping"						
but a kick in the teeth may be the best thing in the world for	/ou"}, [74.125.19.54 [30/Nov/2013:11:13:14 -0800] "GET / HTTP/1.1" 200 1	992 "-					
8 { author : 'Unknown', text : "Even the greatest was once a begin	<pre>ner. Don' Mozilla/5.0 (Macintosh; U; Intel Mac OS X 10.5; en-US; rv:1.9.0.4) Ge</pre>	ecko/2					
t be afraid to take that first step."},	102920 Firefox/3.0.4 chartbeat/uptimeping"						
7 { author : 'Neale Donald Walsch', text : "You are afraid to die,	and you' 74.125.40.20 [30/Nov/2013:11:13:16 -0800] "GET /arguments/feed/fe	eed.xm					
re afraid to live. What a way to exist."}	TTP/1.1" 301 178 "-" "FeedBurner/1.0 (http://www.FeedBurner.com)"						
6];	74.125.176.54 [30/Nov/2013:11:13:16 -0800] "GET /arguments/feed/	feed.x					
5	HTTP/1.1" 200 703 "-" "FeedBurner/1.0 (http://www.FeedBurner.com)"						
4 app.listen(8080, '4.2.2.2');	74.125.183.197 [30/Nov/2013:11:13:17 -0800] "GET /blog/bastids/fe	eed H1					
3	1.1" 200 2329 "-" "Mozilla/5.0 (compatible; Googlebot/2.1; +http://ww	ww.goo					
<pre>2 app.get('/', function(req, res) {</pre>	.com/bot.html)"	.com/bot.html)"					
<pre>1 res.json(quotes);</pre>	Waiting for data (interrupt to abort)						
0 })							
1							
<pre>2 app.get('/quote/random', function(req, res) {</pre>	1 [0.7%] Tasks: 37, 29 thr; 1 running						
<pre>3 var id = Math.floor(Math.random() * quotes.length);</pre>	2 [0.7%] Load average: 0.00 0.01 0.00						
4 var q = quotes[id];	3 [0.0%] Uptime: 35 days, 06:43:50	3 [0.0%] Uptime: 35 days, 06:43:50					
5 res.json(q);	4 [0.0%]						
6));	Mem[
7	Swp[124/2048MB]						
<pre>8 app.get('/quote/:id', function(req, res) {</pre>		_					
9 if(quotes.length <= req.params.id req.params.id < 0) {	Send signal: PID USER PRI NI VIRT RES SHR S CPU% MEM%	TI					
10 res.statusCode = 404;	9 SIGKILL 1 root 20 0 24164 1208 480 S 0.0 0.1	0:0					
<pre>11 return res.send('Error 404: No quote found');</pre>	10 SIGUSR1 30268 syslog 20 0 173M 1580 1084 S 0.0 0.1	0:0					
	111 SIGSEGV 302/1 syslog 20 0 1/3M 1580 1084 S 0.0 0.1	0:0					
12 }		0:0					
12 3	12 51605RZ 30000 FOOL 20 0 19844 1510 1092 5 0.0 0.1	0:10					
12 ; 13 14 var q = quotes[req.params.id];	13 SIGPIPE 30065 www-data 20 0 20024 1560 944 S 0.0 0.1						
12 ; 13 14 var q = quotes[req.params.id]; 15 res.json(q);	12 SIGUSK2 36065 www-data 20 61 904 H 1510 1692 S 6.0 0.1 13 SIGPIPE 30065 www-data 20 0 20824 1560 944 S 0.0 0.1 14 SIGALRM 30064 www-data 20 0 20824 1560 1372 S 0.0 0.1	1:5					
/2 J 14 var q = quotes[req.params.id]; 15 res.json(q); 10RMAL quote.js + unix utf-8 javascript 36% L	Instructure Second Foot Cold Bit Second Foot S	1:5 1:5					
12 j 13 14 var q = quotes[req.params.id]; 15 res.json(q); NORMAL quote.js + unix utf-8 javascript 36% L	In 2 Sicontz 38666 TOOL 20 9 13644 In 10 105 2 3 0.0 0.1 113 Sicontz 38666 TOOL 20 0 20824 1560 9445 0.0 0.1 14 SicALRM 30064 www-data 20 0 20824 1372 5 0.0 0.1 153 15 SicTERM 30063 www-data 20 0 20855 2732 1380 S 0.0 0.1 IEnter\$end EscCance1 20 20855 2732 1380 S 0.0 0.1	1:54 1:53					

One of these features is the ability to break your session into more discreet components, called windows and panes. These are good for organizing multiple varied activities in a logical way.

Let's look at how they relate to each other.

Nesting



tmux sessions have windows, and windows have panes. Below you can see how how I conceptualize them—although if anyone has a more authoritative or useful hierarchy I'll happily embrace it.

- Sessions are for an overall *theme*, such as *work*, or *experimentation*, or *sysadmin*.
- Windows are for *projects* within that theme. So perhaps within your *experimentation* session you have a window titled *noderestapi*, and one titled *lua sample*.
- **Panes** are for *views* within your current project. So within your *sysadmin* session, which has a *logs* window, you may have a few panes for access logs, error logs, and system logs.

It's also possible to create panes within a session without first creating a separate window. I do this sometimes. Hopefully it isn't as horrible as it sounds right after reading about nesting. As I said in the beginning, I incline towards simplicity with my use of tmux.

Navigating with panes

There's a default way to navigate between panes, but I don't know what it is. I'm a <u>vim</u> guy, so I navigate within my panes using the h, j, k, and l keys like so:

Remap window navigation to vim unbind-key j bind-key j select-pane -D unbind-key k bind-key k select-pane -U unbind-key h bind-key h select-pane -L unbind-key l

Recommendations

A few thoughts that may help you in your tmux travels:

- 1. Consider using as few sessions and windows as possible. Humans aren't as good at multitasking as we think we are, and while it feels powerful to have 47 panes open it's usually not as functional as you'd imagine.
- 2. When you do use windows and panes, take the time to name them. They are indeed useful, but switching between sessions and windows is supremely annoying when they're all labeled 0, 1, and 2.
- 3. Start with a basic config and get used to it before you get silly. I've seen multiple people spend hours configuring vim or tmux only to confuse themselves and abandon the project altogether. Start simple.

Shortcut Reference

Now a Ctrl-b options reference:

Basics

• ? get help

Session management

- **s** list sessions
- **\$** rename the current session
- **d** detach from the current session

Windows

- c create a new window
- , rename the current window
- w list windows
- % split horizontally
- " split vertically
- **n** change to the next window
- **p** change to the previous window

Panes

- % create a horizontal pane
- " create a vertical pane
- **h** move to the left pane. *
- j move to the pane below *
- 1 move to the right pane *
- k move to the pane above *
- k move to the pane above *
- **q** show pane numbers
- • toggle between panes
- } swap with next pane
- { swap with previous pane
- ! break the pane out of the window
- **x** kill the current pane

Miscellaneous

• **t** show the time in current pane

I hope this has been helpful.

[If you liked this, check out my other technical primers here.]

Resources

- 1. The man page.
- 2. A thousand other great tutorials.

2	17	164	18		
-	-	-	-		
Share	Share	Share	Share	Share	Share

Related...

- <u>9 Enhancements to Shell and Vim Productivity</u>
- From iTerm2 to Terminal.app
- Port Mirroring on a Cisco 3550 Switch
- <u>Annoying Things in OS X</u>

Enter your email address

```
Subscribe
```

Have an opinion on this?

If so, I'd love to hear from you on Twitter, via email, or in the comments below.

22 Comments danielmiessler.com Login Sort by Best Share 🖄 Favorite ★ Image: Comment of the discussion...